



COLORBODY™ PORCELAIN

TERRACE™

Professional  
TILE SOLUTIONS



daltile®

# COLORBODY™ PORCELAIN TERRACE™



*floor • wall • countertop*

Experience the countryside with the new Daltile Terrace collection. This ColorBody™ Porcelain tile has the look of natural wood with a contemporary edge - perfect for high-traffic areas. Available in a contemporary plank size, it's on-trend, extremely durable, and easier to maintain than traditional wood floors. Ideal for commercial installations due to its versatile nature, this fashionable wood-look tile can give your residential space a contemporary flair as well. Surround yourself in the warm hues of this collection, available in six colors. Create ambiance and perfect your space.



Photo features Terrace Cherry 6 x 36 field tile in a staggered brickwork pattern on the floor.

*floor • wall • countertop*

# COLORBODY™ PORCELAIN

TERRACE™

*Field Tile*



BIANCO P100



HICKORY P101



GOLD P102



WALNUT P103



CHERRY P104




ESPRESSO P105

# CREATIVE IDEAS


## Decorative Accents




## Pattern Ideas




STAGGERED BRICKWORK



HERRINGBONE



CORRIDOR HORIZONTAL



BASKETWEAVE

# COLORBODY™ PORCELAIN

# TERRACE™

## SIZES

		SQ.FT. CARTON	PIECES PER CARTON
6 x 36 Field Tile	5-3/4" x 35-3/4" (14.6 cm x 90.8 cm)	12.00	8

Additional linear and rectangular sizes available through Linear Options™ - Daltile's linear cutting service. Visit [www.daltile.com/lineartoptions](http://www.daltile.com/lineartoptions) for sizes and order information.

## RESIDENTIAL USAGE

FLOOR	WALL	COUNTERTOPS	EXTERIOR PATIOS	EXTERIOR POOL DECKS
F	W	C	EP	<del>ED</del>

Suitable for exterior floors (excluding pool decks) and walls in freezing and non-freezing climates when proper installation methods are followed.

## COMMERCIAL APPLICATION

	LIGHT COMMERCIAL	COMMERCIAL	COMMERCIAL EXTERIORS
Floors	◆	◆	
Walls/Backsplashes	◆	◆	◆
Countertops	◆	◆	◆
Pool Decking			
Pool Linings	◆	◆	◆

Suitable for exterior walls in freezing and non-freezing climates when proper installation methods are followed.

## NOTES


Special care should be taken when grouting dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the surface. Use of a latex modified thin-set is recommended for installation.

Since there are variations in all fired ceramic products, tile and trim supplied for your particular installation may not match these samples. Final color selection should be made from actual tiles and trim and not from tile and trim samples or color reproductions. Manufactured in accordance with ANSI A 137.1 standards.

For additional information, refer to "Factors to Consider" at [www.daltile.com/CommercialFactors](http://www.daltile.com/CommercialFactors).

Water, oil, grease, etc. create slippery conditions. Floor applications with exposure to these conditions require extra caution in product selection.  
Not for use on ramps.

## TRIM

TYPE	NUMBER	SIZE	PCS. PER CARTON
 Bullnose	S-43H9	3 x 18	32

## SHADE VARIATION



High (V3)  
Color variation from tile to tile, and within each tile.

## INSTALLATION

THICKNESS	GROUT JOINT RECOMMENDATION
1/2"	3/16" Floor

## SLIP RESISTANCE (WET) : 3

The higher the rating, the higher the slip resistance.

1	< .50
2	< .50 .50 - .59
<b>3</b>	≥ .60

## TEST RESULTS

	ASTM#	RESULTS
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 400 lbs
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant
Coefficient of Friction	CI028	Wet: ≥ 0.60 Dry: ≥ 0.70

# COLORBODY™ PORCELAIN

# TERRACE™



*floor • wall • countertop*



By their very design, Daltile products can help make it easier for you to earn LEED™ points and/or points towards many industry leading green home building programs. From using recycled material content to establishing manufacturing facilities within 500 miles of your project, we help ensure you don't have to compromise your design to be environmentally conscious. For detailed information, visit [daltilegreenworks.com](http://daltilegreenworks.com).

*Professional*  
TILE SOLUTIONS



Printed using soy inks.



7834 C. F. Hawn Freeway | Dallas, TX 75217 | 214.398.1411 800.933.TILE  
For more information about Daltile products and services, visit our website at [daltile.com](http://daltile.com)

©2010 DalTile Corporation (10/10) SSPTERRAC